
ARES, thanks to its discreet and elegant line, fits perfectly into any type of furniture. Practicality and reliability complete ARES. Available in 4 heights and 8 widths from 380 to 750 mm, also in the version with 50 mm connections. With the insertion of the electric resistance (optional) it can work even in periods when the system is off.



Ares, Hight 1462 mm, Lenght 530 mm, Standard White

Construction features

steel towel warmer radiator with horizontal elements featuring round tubes
with a 23 mm diameter
side manifolds with a 40x30 mm semioval section
manifold threading and central connections (50 mm) 1/2" Gas right
maximum working pressure 8 bar
maximum working temperature 95°C

Standard equipment

3 infratube for wall fixing
1/2" air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}C$ (btu/h)	$\Delta t=50^{\circ}C$ (kcal/h)	$\Delta t=50^{\circ}C$ (Watt)	$\Delta t=40^{\circ}C$ (Watt)	$\Delta t=30^{\circ}C$ (Watt)	$\Delta t=20^{\circ}C$ (Watt)	Exponent	mixed oper. (Watt)
01														
818 15 rails 2 espaces	30,0	818	380	350	4,20	3,10	995,0	251,0	292,0	223,0	158,0	97,0	1,206	300
818 15 rails 2 espaces	30,0	818	430	400	4,50	3,40	1.106,0	279,0	324,0	248,0	175,0	107,0	1,207	300
818 15 rails 2 espaces	30,0	818	480	450	4,90	3,70	1.208,0	304,0	354,0	270,0	191,0	117,0	1,207	300
818 15 rails 2 espaces	30,0	818	500	470	5,10	3,80	1.248,0	315,0	366,0	280,0	198,0	121,0	1,207	400
818 15 rails 2 espaces	30,0	818	530	500	5,30	4,00	1.310,0	330,0	384,0	293,0	207,0	127,0	1,206	400
818 15 rails 2 espaces	30,0	818	580	550	5,70	4,20	1.411,0	356,0	414,0	316,0	223,0	137,0	1,206	400
818 15 rails 2 espaces	30,0	818	600	570	5,80	4,30	1.452,0	366,0	426,0	325,0	230,0	141,0	1,206	400
818 15 rails 2 espaces	30,0	818	750	720	9,00	4,80	1.757,0	443,0	515,0	393,0	278,0	171,0	1,206	400
1118 22 rails 2 espaces	30,0	1118	380	350	5,90	4,50	1.420,0	358,0	416,0	318,0	224,0	137,0	1,213	400
1118 22 rails 2 espaces	30,0	1118	430	400	6,40	4,90	1.556,0	392,0	456,0	346,0	243,0	147,0	1,233	400
1118 22 rails 2 espaces	30,0	1118	480	450	7,00	5,20	1.709,0	431,0	501,0	381,0	268,0	163,0	1,228	400
1118 22 rails 2 espaces	30,0	1118	500	470	7,20	5,40	1.774,0	447,0	520,0	395,0	278,0	169,0	1,227	400
1118 22 rails 2 espaces	30,0	1118	530	500	7,50	5,60	1.866,0	470,0	547,0	416,0	293,0	178,0	1,224	400
1118 22 rails 2 espaces	30,0	1118	580	550	8,10	6,00	2.023,0	510,0	593,0	452,0	318,0	194,0	1,220	400

1118 22 rails 2 espaces	30,0	1118	600	570	8,30	6,20	2.088,0	526,0	612,0	466,0	329,0	201,0	1,218	400
1118 22 rails 2 espaces	30,0	1118	750	720	12,90	7,00	2.556,0	644,0	749,0	572,0	405,0	248,0	1,205	700
1462 28 rails 3 espaces	30,0	1462	380	350	7,60	5,80	1.846,0	465,0	541,0	412,0	290,0	176,0	1,223	400
1462 28 rails 3 espaces	30,0	1462	430	400	8,30	6,20	2.020,0	509,0	592,0	450,0	316,0	192,0	1,227	400
1462 28 rails 3 espaces	30,0	1462	480	450	8,90	6,80	2.221,0	560,0	651,0	495,0	348,0	212,0	1,226	700
1462 28 rails 3 espaces	30,0	1462	500	470	9,20	7,00	2.300,0	580,0	674,0	513,0	360,0	219,0	1,226	700
1462 28 rails 3 espaces	30,0	1462	530	500	9,60	7,20	2.422,0	611,0	710,0	540,0	380,0	231,0	1,225	700
1462 28 rails 3 espaces	30,0	1462	580	550	10,30	7,70	2.624,0	661,0	769,0	585,0	411,0	250,0	1,224	700
1462 28 rails 3 espaces	30,0	1462	600	570	10,60	7,90	2.702,0	681,0	792,0	603,0	424,0	258,0	1,224	700
1462 28 rails 3 espaces	30,0	1462	750	720	16,50	8,90	3.304,0	833,0	968,0	737,0	519,0	316,0	1,221	1000
1720 34 rails 3 espaces	30,0	1720	380	350	9,10	6,90	2.208,0	556,0	647,0	493,0	347,0	212,0	1,217	700
1720 34 rails 3 espaces	30,0	1720	430	400	9,90	7,50	2.429,0	612,0	712,0	541,0	380,0	231,0	1,227	700
1720 34 rails 3 espaces	30,0	1720	480	450	10,70	8,10	2.668,0	673,0	782,0	595,0	418,0	255,0	1,225	700
1720 34 rails 3 espaces	30,0	1720	500	470	11,10	8,30	2.767,0	697,0	811,0	617,0	434,0	264,0	1,224	700
1720 34 rails 3 espaces	30,0	1720	530	500	11,60	8,70	2.910,0	734,0	853,0	649,0	457,0	278,0	1,223	700
1720 34 rails 3 espaces	30,0	1720	580	550	12,40	9,30	3.149,0	794,0	923,0	703,0	495,0	302,0	1,220	1000
1720 34 rails 3 espaces	30,0	1720	600	570	12,70	9,50	3.248,0	819,0	952,0	725,0	511,0	311,0	1,220	1000

1720 34 rails 3 espaces	30,0	1720	750	720	19,90	10,70	3.968,0	1.000,0	1.163,0	887,0	626,0	383,0	1,213	1000
05														
818 15 rails 2 espaces	30,0	818	380	350	4,20	3,10	995,0	251,0	292,0	223,0	158,0	97,0	1,206	300
818 15 rails 2 espaces	30,0	818	430	400	4,50	3,40	1.106,0	279,0	324,0	248,0	175,0	107,0	1,207	300
818 15 rails 2 espaces	30,0	818	480	450	4,90	3,70	1.208,0	304,0	354,0	270,0	191,0	117,0	1,207	300
818 15 rails 2 espaces	30,0	818	500	470	5,10	3,80	1.248,0	315,0	366,0	280,0	198,0	121,0	1,207	400
818 15 rails 2 espaces	30,0	818	530	500	5,30	4,00	1.310,0	330,0	384,0	293,0	207,0	127,0	1,206	400
818 15 rails 2 espaces	30,0	818	580	550	5,70	4,20	1.411,0	356,0	414,0	316,0	223,0	137,0	1,206	400
818 15 rails 2 espaces	30,0	818	600	570	5,80	4,30	1.452,0	366,0	426,0	325,0	230,0	141,0	1,206	400
818 15 rails 2 espaces	30,0	818	750	720	9,00	4,80	1.757,0	443,0	515,0	393,0	278,0	171,0	1,206	400
1118 22 rails 2 espaces	30,0	1118	380	350	5,90	4,50	1.420,0	358,0	416,0	318,0	224,0	137,0	1,213	400
1118 22 rails 2 espaces	30,0	1118	430	400	6,40	4,90	1.556,0	392,0	456,0	346,0	243,0	147,0	1,233	400
1118 22 rails 2 espaces	30,0	1118	480	450	7,00	5,20	1.709,0	431,0	501,0	381,0	268,0	163,0	1,228	400
1118 22 rails 2 espaces	30,0	1118	500	470	7,20	5,40	1.774,0	447,0	520,0	395,0	278,0	169,0	1,227	400
1118 22 rails 2 espaces	30,0	1118	530	500	7,50	5,60	1.866,0	470,0	547,0	416,0	293,0	178,0	1,224	400
1118 22 rails 2 espaces	30,0	1118	580	550	8,10	6,00	2.023,0	510,0	593,0	452,0	318,0	194,0	1,220	400
1118 22 rails 2 espaces	30,0	1118	600	570	8,30	6,20	2.088,0	526,0	612,0	466,0	329,0	201,0	1,218	400
1118 22 rails 2 espaces	30,0	1118	750	720	12,90	7,00	2.556,0	644,0	749,0	572,0	405,0	248,0	1,205	700
1462 28 rails 3 espaces	30,0	1462	380	350	7,60	5,80	1.846,0	465,0	541,0	412,0	290,0	176,0	1,223	400

1462 28 rails 3 espaces	30,0	1462	430	400	8,30	6,20	2.020,0	509,0	592,0	450,0	316,0	192,0	1,227	400
1462 28 rails 3 espaces	30,0	1462	480	450	8,90	6,80	2.221,0	560,0	651,0	495,0	348,0	212,0	1,226	700
1462 28 rails 3 espaces	30,0	1462	500	470	9,20	7,00	2.300,0	580,0	674,0	513,0	360,0	219,0	1,226	700
1462 28 rails 3 espaces	30,0	1462	530	500	9,60	7,20	2.422,0	611,0	710,0	540,0	380,0	231,0	1,225	700
1462 28 rails 3 espaces	30,0	1462	580	550	10,30	7,70	2.624,0	661,0	769,0	585,0	411,0	250,0	1,224	700
1462 28 rails 3 espaces	30,0	1462	600	570	10,60	7,90	2.702,0	681,0	792,0	603,0	424,0	258,0	1,224	700
1462 28 rails 3 espaces	30,0	1462	750	720	16,50	8,90	3.304,0	833,0	968,0	737,0	519,0	316,0	1,221	1000
1720 34 rails 3 espaces	30,0	1720	380	350	9,10	6,90	2.208,0	556,0	647,0	493,0	347,0	212,0	1,217	700
1720 34 rails 3 espaces	30,0	1720	430	400	9,90	7,50	2.429,0	612,0	712,0	541,0	380,0	231,0	1,227	700
1720 34 rails 3 espaces	30,0	1720	480	450	10,70	8,10	2.668,0	673,0	782,0	595,0	418,0	255,0	1,225	700
1720 34 rails 3 espaces	30,0	1720	500	470	11,10	8,30	2.767,0	697,0	811,0	617,0	434,0	264,0	1,224	700
1720 34 rails 3 espaces	30,0	1720	530	500	11,60	8,70	2.910,0	734,0	853,0	649,0	457,0	278,0	1,223	700
1720 34 rails 3 espaces	30,0	1720	580	550	12,40	9,30	3.149,0	794,0	923,0	703,0	495,0	302,0	1,220	1000
1720 34 rails 3 espaces	30,0	1720	600	570	12,70	9,50	3.248,0	819,0	952,0	725,0	511,0	311,0	1,220	1000
1720 34 rails 3 espaces	30,0	1720	750	720	19,90	10,70	3.968,0	1.000,0	1.163,0	887,0	626,0	383,0	1,213	1000

Thanks to the high performance of Irsap ARES radiators, the ideal Δt for low temperature projects is Δt at 30°C.


For Δt different from 50°C use the formula: Q=Qn (Δt / 50)n

Standard equipment

- 3 infratube for wall fixing • 1/2" air vent


Colors and Finishes

STANDARD



Standard White
Cod. 01

CLASSIC




Edelweiss White
Cod. 34



Ivory - RAL 1013
Cod. 02



Beige Cream
Cod. 26



Yellow - RAL 1021
Cod. 04




Melon Yellow - RAL 1028
Cod. E7



Orange - RAL 2004
Cod. 17



Brown Rust - RAL 8004
Cod. E1



Brown - RAL 8017
Cod. 09



Claret - RAL 3003
Cod. 06



Red - RAL 3000
Cod. 05



Strawberry Red - RAL 3018
Cod. Y3



Pink - RAL 3015
Cod. R2



Bluish Lilac - RAL 4005
Cod. R3



Purple Traffic - RAL 4006
Cod. R6




Woodland Green - RAL 6005
Cod. 19



Green Grass - RAL 6018
Cod. N3




Sage Green - RAL 6021
Cod. E6




Pastel Blue - RAL 5024
Cod. G7



Manhattan Grey
Cod. 03




Black - RAL 9005
Cod. 10



Deep Blue
Cod. 2F

SPECIAL



Pearl White
Cod. 16



Quartz 1
Cod. 1C



Sablé
Cod. Y4



Quartz 2
Cod. 2C



Sunstone
Cod. 2D









Tobacco Brown
Cod. 1B



Flame Red
Cod. 7D



Purple Blue
Cod. 1D

							
Azurite 3 Cod. 6C	Medium Grey Cod. 4D	Titanium Grey Metallic - RAL 9023 Cod. L3	Pearl Grey Cod. L6	Graphite Black Cod. 18	Quartz Grey Cod. 31	Satin Black Cod. 30	Matt White Cod. J8
							
Matt Black Cod. K1	Agave Cod. 9N	North Sea Blue Cod. 1P	Ice Cod. 3P	Matt Blue Dove - RAL 5014 Cod. 4P	Matt Light Grey Cod. 8N	Ash Grey - Ral 7021 Cod. G1	Hammered Grey Metallic Cod. 32
							
Hammered Copper Cod. J4							

RAL



Other RAL Colours (following feasibility study)
Cod. ALTRIRAL

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.