# **Blues**



Stainless steel radiator characterized by horizontal elements and an essential and elegant ensemble, which enriches the bathroom not only with a heating element but also with a decorative object. BLUES is available in two finishes: mirror stainless steel and satin stainless steel.



Blues, Hight 1400 mm, Lenght 500 mm, Chromium

## **Construction features**

stainless steel towel warmer radiator with 15x30 mm rectangular tube horizontal elements side manifolds with 30x30 mm square section threading at the ends of the lower manifolds, 1/2" Gas right maximum working pressure 4 bar maximum working temperature 95°C

## Standard equipment

4 wall fixings 2 air vent valves of 1/2"

## **Certifications**

# Plus











## **Technical data**

Model	Deph	Height	Width	Conn. C.	Weigth	Capacity	Δt=50°C (btu/h)	Δt=50°C (kcal/h)	Δt=50°C (Watt)	Δt=40°C (Watt)	Δt=30°C (Watt)	Δt=20°C (Watt)	Exponent
	(mm)	(mm)	(mm)	(mm)	(kg)	(It)	(btu/II)	(KCal/II)	(vvaii)	(vvaii)	(vvaii)	(vvaii)	
770 14 rails 3 espaces	45,0	770	500	50	6,20	3,60	764,0	193,0	224,0	168,0	116,0	69,0	1,290
1190 20 rails 5 espaces	s 45,0	1190	500	50	8,90	5,30	1.118,0	282,0	328,0	245,0	168,0	99,0	1,310
1400 24 rails 6 espaces	s 45,0	1400	500	50	10,60	6,40	1.326,0	335,0	389,0	288,0	196,0	114,0	1,340
1700 28 rails	s 45,0	1700	500	50	12,40	7,60	1.569,0	396,0	460,0	340,0	231,0	134,0	1,350

(\*) Thanks to the high performance of Irsap BLUES radiators, the ideal Δt for low temperature projects is Δt at 30°C.

For  $\Delta t$  different from 50°C use the formula: Q=Qn ( $\Delta t$  / 50)n

#### Standard equipment

• 4 wall fixings • 2 air vent valves of 1/2"

## **Colors and Finishes**

#### **FINISHES**



The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.