

---

Lines that chase each other forming a geometric sign of high personality. Precisely worked steel characterizes DEDALO with a defined personality. The LED light (in the model with light) creeps into the spaces, forming plays of light and shadow. It is supplied with the innovative concealed hydraulic connection system installed directly in the company. Available in two models, DEDALO P and DEDALO L, with two thermal powers.



Dedalo, Hight 1600 mm, Lenght 660 mm, Matt Blue Dove - RAL 5014

## **Construction features**

radiating panel

1/2" Gas right threading

maximum working pressure 4 bar

maximum working temperature 95°C

## **Standard equipment**

innovative water connection system installed on the product complete

with fittings for connection to copper pipes (12, 14 and 15 mm diameter) and multilayer pipes (14 x 2 thick and 16 x 2 thick)

wall fixing system built into the product column

LED lighting system optional

air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}\text{C}$ (btu/h)	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent
Dedalo	90,0	900	498	50	18,00	0,70	846,0	213,0	248,0	182,0	122,0	70,0	1,386
Dedalo with led	90,0	900	498	50	18,00	0,70	846,0	213,0	248,0	182,0	122,0	70,0	1,386
Dedalo	90,0	1600	660	50	23,20	1,40	2.269,0	563,0	665,0	509,0	361,0	223,0	1,194
Dedalo with led	90,0	1600	660	50	23,20	1,40	2.269,0	563,0	665,0	509,0	361,0	223,0	1,194

Thanks to the high performance of Irsap DEDALO radiators, the ideal  $\Delta t$  for low temperature projects is  $\Delta t$  at  $30^{\circ}\text{C}$ .

For  $\Delta t$  different from  $50^{\circ}\text{C}$  use the formula  $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- innovative water connection system installed on the product complete with fittings for connection to copper pipes (12, 14 and 15 mm diameter) and multilayer pipes (14 x 2 thick and 16 x 2 thick)
- wall fixing system built into the product column
- LED lighting system optional
- air vent



Colors and Finishes

SPECIAL

							
<b>Pearl White</b> Cod. 16	<b>Quartz 1</b> Cod. 1C	<b>Sablé</b> Cod. Y4	<b>Quartz 2</b> Cod. 2C	<b>Sunstone</b> Cod. 2D	<b>Tobacco Brown</b> Cod. 1B	<b>Flame Red</b> Cod. 7D	<b>Purple Blue</b> Cod. 1D
							
<b>Azurite 3</b> Cod. 6C	<b>Medium Grey</b> Cod. 4D	<b>Titanium Grey Metallic - RAL 9023</b> Cod. L3	<b>Pearl Grey</b> Cod. L6	<b>Graphite Black</b> Cod. 18	<b>Quartz Grey</b> Cod. 31	<b>Satin Black</b> Cod. 30	<b>Matt White</b> Cod. J8
							
<b>Matt Black</b> Cod. K1	<b>Agave</b> Cod. 9N	<b>North Sea Blue</b> Cod. 1P	<b>Ice</b> Cod. 3P	<b>Matt Blue Dove - RAL 5014</b> Cod. 4P	<b>Matt Light Grey</b> Cod. 8N	<b>Ash Grey - Ral 7021</b> Cod. G1	<b>Hammered Grey Metallic</b> Cod. 32
							
<b>Hammered Copper</b> Cod. J4							

RAL



Other RAL Colours (following feasibility study)  
Cod. ALTRIRAL

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.