
FACE_AIR is a steel radiant plate. Small integrated silenced fans add power to the radiator performance. The heating body hides all fasteners, connections and electrical connections from view. The exclusive stainless steel finishes give FACE_AIR the elegance of a single piece, while the colors of the IRSAP range offer perfect continuity with the stylistic key of the environment.



Face Air, Hight 1800 mm, Lenght 600 mm, Fabric Blue

Construction features

- radiating panel
- 1/2" Gas right threading
- maximum working pressure 4 bar
- maximum working temperature 95°C
- radial fans with low fuel motors

Standard equipment

- 2 lockshield valves 1/2" M 1/2" F – FE connection
- flexible pipes for ease of installation
- wall fastening system
- power supply unit
- modulating thermostatic head

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}\text{C}$ (btu/h)	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent
FACE_Air 1600 x 500	75,0	1597	500	50	31,90	1,20	2.559,0	645,0	750,0	569,0	398,0	241,0	1,240
FACE_Air 1600 x 600	75,0	1597	598	50	38,80	1,60	3.412,0	860,0	1.000,0	760,0	533,0	324,0	1,230
FACE_Air 1800 x 500	75,0	1797	500	50	36,70	1,40	3.207,0	808,0	940,0	713,0	499,0	302,0	1,240
FACE_Air 1800 x 600	75,0	1797	598	50	43,60	1,80	4.163,0	1.049,0	1.220,0	927,0	651,0	395,0	1,230

(*) Thanks to the high performance of Irsap FACE_AIR radiators, the ideal Δt for low temperature projects is Δt at 30°C.


For Δt different from 50°C use the formula: $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- 2 lockshield valves 1/2" M 1/2" F – FE connection
- flexible pipes for ease of installation
- wall fastening system
- power supply unit
- modulating thermostatic head


Colors and Finishes

STANDARD



Standard White
Cod. 01

CLASSIC



Edelweiss White
Cod. 34



Ivory - RAL 1013
Cod. 02



Beige Cream
Cod. 26




Yellow - RAL 1021
Cod. 04



Melon Yellow - RAL 1028
Cod. E7



Orange - RAL 2004
Cod. 17



Brown Rust - RAL 8004
Cod. E1



Brown - RAL 8017
Cod. 09




Claret - RAL 3003
Cod. 06



Red - RAL 3000
Cod. 05



Strawberry Red - RAL 3018
Cod. Y3



Pink - RAL 3015
Cod. R2



Bluish Lilac - RAL 4005
Cod. R3



Purple Traffic - RAL 4006
Cod. R6



Woodland Green - RAL 6005
Cod. 19



Green Grass - RAL 6018
Cod. N3




Sage Green - RAL 6021
Cod. E6




Pastel Blue - RAL 5024
Cod. G7



Manhattan Grey
Cod. 03




Black - RAL 9005
Cod. 10



Deep Blue
Cod. 2F

SPECIAL




Pearl White
Cod. 16




Quartz 1
Cod. 1C



Sablé
Cod. Y4



Quartz 2
Cod. 2C



Sunstone
Cod. 2D










Tobacco Brown
Cod. 1B






Flame Red
Cod. 7D



Purple Blue
Cod. 1D

							
Azurite 3 Cod. 6C	Medium Grey Cod. 4D	Titanium Grey Metallic - RAL 9023 Cod. L3	Pearl Grey Cod. L6	Graphite Black Cod. 18	Quartz Grey Cod. 31	Satin Black Cod. 30	Matt White Cod. J8
							
Matt Black Cod. K1	Agave Cod. 9N	North Sea Blue Cod. 1P	Ice Cod. 3P	Matt Blue Dove - RAL 5014 Cod. 4P	Matt Light Grey Cod. 8N	Ash Grey - Ral 7021 Cod. G1	Hammered Grey Metallic Cod. 32

FINISHES

			
Fabric Blue Cod. 1G	Black Dots Cod. 2G	Satin Black Cod. 3G	Glossy Linen Cod. 4G

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.