

Form and function, calm, simplicity are the inspiring muses of the IT IS radiator. Harmony, rhythm, balance between full and empty, perfect proportions, the most meticulous attention to detail make the architectural structure of IT IS clear and legible, giving it a sense of freshness, cleanliness and order.



It Is, Hight 1208 mm, Lenght 500 mm, Chromium

## **Construction features**

horizontal elements featuring rectangular tubes 60x20 mm section  
side manifolds with a 70x20 mm squared section  
3/8" Gas right threading  
maximum working pressure 4 bar  
maximum working temperature 95°C

## **Standard equipment**

angle pattern valve and lockshield valve assembly complete  
with copper fitting (diameters 12, 14 and 15 mm), multilayer  
pipes (14 x 2 thick and 16 x 2 thick)  
kit of pipe covers (suitable for pipes up to 16 mm thick)  
wall fixing system  
air vent chrome-plated  
1 towel rail bracket to match the radiator

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	Δt=50°C (btu/h)	Δt=50°C (kcal/h)	Δt=50°C (Watt)	Δt=40°C (Watt)	Δt=30°C (Watt)	Δt=20°C (Watt)	Exponent
812 13 tubi 70,0		812	500	50	11,10	1,40	1.146,0	289,0	336,0	254,0	177,0	107,0	1,250
812 13 tubi 70,0		812	600	50	13,00	1,60	1.392,0	351,0	408,0	310,0	218,0	132,0	1,230
1208 19 tubi	70,0	1208	500	50	16,30	2,00	1.730,0	436,0	507,0	385,0	270,0	164,0	1,230
1208 19 tubi	70,0	1208	600	50	19,00	2,30	1.976,0	498,0	579,0	440,0	309,0	188,0	1,230
1736 27 tubi	70,0	1736	500	50	23,20	2,80	2.532,0	638,0	742,0	563,0	394,0	238,0	1,240
1736 27 tubi	70,0	1736	600	50	27,10	3,30	2.781,0	701,0	815,0	618,0	433,0	262,0	1,240

(\*) Thanks to the high performance of Irsap IT IS radiators, the ideal Δt for low temperature projects is Δt at 30°C.

For Δt different from 50°C use the formula:  $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- angle pattern valve and lockshield valve assembly complete with copper fitting (diameters 12, 14 and 15 mm), multilayer pipes (14 x 2 thick and 16 x 2 thick) • kit of pipe covers (suitable for pipes up to 16 mm thick) • wall fixing system • air vent chrome-plated • 1 towel rail bracket to match the radiator

FINISHES



**Chromium**  
Cod. 50

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.