

# Novo chrome-plated

---

**IRSAP**

The minimalist style, in the chromed version and with 23 mm tubes, make NOVO CHROME-PLATED an unconventional towel warmer. With the insertion of the electric resistance (optional) it can work even in periods when the system is off.



Novo Cromato, Hight 1800 mm, Lenght 600 mm, Chromium

## **Construction features**

steel towel warmer radiator with horizontal elements featuring  
round tubes 23 mm diameter  
side manifolds with semi-oval section 40x30 mm  
manifold threading and central connections (50 mm) 1/2" Gas right  
maximum working pressure 8 bar  
maximum working temperature 95°C

## **Standard equipment**

pair of Chrome-plated CHELA wall brackets  
wall spacers  
1/2" chrome-plated air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C- (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}\text{C}$ (btu/h)	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent	mixed oper. (Watt)
01														
764 19 rails 1 espace	30,0	764	450	406	5,30	3,90	914,0	230,0	268,0	203,0	142,0	86,0	1,245	-
764 19 rails 1 espace	30,0	764	500	456	5,80	4,30	1.001,0	252,0	293,0	222,0	155,0	94,0	1,244	300
764 19 rails 1 espace	30,0	764	600	556	6,70	5,00	1.175,0	296,0	344,0	261,0	183,0	110,0	1,243	300
764 19 rails 1 espace	30,0	764	750	706	10,70	5,60	1.434,0	362,0	420,0	319,0	223,0	135,0	1,241	400
1196 29 rails 2 espaces	30,0	1196	450	406	8,10	6,10	1.218,0	307,0	357,0	269,0	186,0	111,0	1,275	300
1196 29 rails 2 espaces	30,0	1196	500	456	8,80	6,60	1.353,0	341,0	396,0	299,0	207,0	124,0	1,272	400
1196 29 rails 2 espaces	30,0	1196	600	556	10,30	7,60	1.627,0	410,0	477,0	359,0	250,0	149,0	1,267	400
1196 29 rails 2 espaces	30,0	1196	750	706	16,40	8,60	2.039,0	514,0	598,0	451,0	314,0	189,0	1,259	400
1520 36 rails 3 espaces	30,0	1520	450	406	10,20	7,60	1.656,0	417,0	485,0	365,0	252,0	150,0	1,279	400
1520 36 rails 3 espaces	30,0	1520	500	456	11,00	8,20	1.821,0	459,0	534,0	401,0	278,0	166,0	1,277	400
1520 36 rails 3 espaces	30,0	1520	600	556	12,80	9,50	2.151,0	542,0	630,0	475,0	329,0	196,0	1,273	700
1520 36 rails 3 espaces	30,0	1520	750	706	20,40	10,80	2.646,0	667,0	776,0	585,0	406,0	243,0	1,266	700
1808 44 rails 3 espaces	30,0	1808	450	406	12,30	9,20	1.976,0	498,0	579,0	436,0	302,0	180,0	1,272	400

1808 44 rails 3 espaces	30,0	1808	500	456	13,30	10,00	2.180,0	549,0	639,0	481,0	334,0	200,0	1,269	700
1808 44 rails 3 espaces	30,0	1808	600	556	15,50	11,50	2.587,0	652,0	758,0	572,0	398,0	238,0	1,262	700
1808 44 rails 3 espaces	30,0	1808	750	706	24,80	13,10	3.198,0	806,0	937,0	709,0	494,0	298,0	1,252	1000
05														
764 19 rails 1 espace	30,0	764	450	406	5,30	3,90	914,0	230,0	268,0	203,0	142,0	86,0	1,245	-
764 19 rails 1 espace	30,0	764	500	456	5,80	4,30	1.001,0	252,0	293,0	222,0	155,0	94,0	1,244	300
764 19 rails 1 espace	30,0	764	600	556	6,70	5,00	1.175,0	296,0	344,0	261,0	183,0	110,0	1,243	300
764 19 rails 1 espace	30,0	764	750	706	10,70	5,60	1.434,0	362,0	420,0	319,0	223,0	135,0	1,241	400
1196 29 rails 2 espaces	30,0	1196	450	406	8,10	6,10	1.218,0	307,0	357,0	269,0	186,0	111,0	1,275	300
1196 29 rails 2 espaces	30,0	1196	500	456	8,80	6,60	1.353,0	341,0	396,0	299,0	207,0	124,0	1,272	400
1196 29 rails 2 espaces	30,0	1196	600	556	10,30	7,60	1.627,0	410,0	477,0	359,0	250,0	149,0	1,267	400
1196 29 rails 2 espaces	30,0	1196	750	706	16,40	8,60	2.039,0	514,0	598,0	451,0	314,0	189,0	1,259	400
1520 36 rails 3 espaces	30,0	1520	450	406	10,20	7,60	1.656,0	417,0	485,0	365,0	252,0	150,0	1,279	400
1520 36 rails 3 espaces	30,0	1520	500	456	11,00	8,20	1.821,0	459,0	534,0	401,0	278,0	166,0	1,277	400
1520 36 rails 3 espaces	30,0	1520	600	556	12,80	9,50	2.151,0	542,0	630,0	475,0	329,0	196,0	1,273	700
1520 36 rails 3 espaces	30,0	1520	750	706	20,40	10,80	2.646,0	667,0	776,0	585,0	406,0	243,0	1,266	700
1808 44 rails 3 espaces	30,0	1808	450	406	12,30	9,20	1.976,0	498,0	579,0	436,0	302,0	180,0	1,272	400
1808 44 rails 3 espaces	30,0	1808	500	456	13,30	10,00	2.180,0	549,0	639,0	481,0	334,0	200,0	1,269	700

1808 44 rails 3 espaces	30,0	1808	600	556	15,50	11,50	2.587,0	652,0	758,0	572,0	398,0	238,0	1,262	700
1808 44 rails 3 espaces	30,0	1808	750	706	24,80	13,10	3.198,0	806,0	937,0	709,0	494,0	298,0	1,252	1000

Thanks to the high performance of Irsap NOVO CHROME PLATED radiators, the ideal  $\Delta t$  for low temperature projects is  $\Delta t$  at 30°C.

For  $\Delta t$  different from 50°C use the formula:  $Q=Q_n (\Delta t / 50)^n$

Irsap guarantees only the hydraulic seal of NOVO CHROME PLATED radiators for 10 years, starting from sales in 2009.

#### Standard equipment

- pair of Chrome-plated CHELA wall brackets • wall spacers • 1/2" chrome-plated air vent

FINISHES



Chromium  
Cod. 50

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.