
Strong personality for a reversible, modern, functional project. This is the singular peculiarity of ODDO, a towel warmer with a frame that summarizes its functionality. The choice of the aesthetic side is personal: the visual inspiration is interpreted at the time of installation, side with flat tube, side with rounded tube. Available in 4 heights and 3 widths. With the insertion of the electric resistance (optional) it can work even in periods when the system is off.



Oddo, Hight 1884 mm, Lenght 600 mm, Quartz 1

Construction features

steel towel warmer radiator with horizontal elements featuring
semi-oval
tubes 40x23 mm diameter
side manifolds with semi-oval section 50x36,5 mm
manifold threading and central connections (50 mm) 1/2" Gas right
maximum working pressure 6 bar
maximum working temperature 95°C
reversible

Standard equipment

4 wall fixing in the same color as the radiator
air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}C$ (btu/h)	$\Delta t=50^{\circ}C$ (kcal/h)	$\Delta t=50^{\circ}C$ (Watt)	$\Delta t=40^{\circ}C$ (Watt)	$\Delta t=30^{\circ}C$ (Watt)	$\Delta t=20^{\circ}C$ (Watt)	Exponent	mixed oper. (Watt)
01														
804 10 rails 1 espace	36,5	804	450	406	8,90	5,90	1.276,0	322,0	374,0	285,0	200,0	122,0	1,224	300
804 10 rails 1 espace	36,5	804	500	456	9,70	6,40	1.396,0	352,0	409,0	311,0	218,0	133,0	1,229	400
804 10 rails 1 espace	36,5	804	600	556	11,20	7,50	1.634,0	412,0	479,0	363,0	254,0	154,0	1,238	400
1224 16 rails 2 espaces	36,5	1224	450	406	13,10	8,70	1.880,0	474,0	551,0	415,0	289,0	173,0	1,265	400
1224 16 rails 2 espaces	36,5	1224	500	456	14,20	9,40	2.061,0	519,0	604,0	455,0	317,0	190,0	1,265	400
1224 16 rails 2 espaces	36,5	1224	600	556	16,40	10,90	2.422,0	611,0	710,0	536,0	372,0	223,0	1,263	700
1584 21 rails 3 espaces	36,5	1584	450	406	16,60	11,00	2.334,0	588,0	684,0	517,0	360,0	216,0	1,258	700
1584 21 rails 3 espaces	36,5	1584	500	456	17,90	11,90	2.569,0	648,0	753,0	569,0	396,0	238,0	1,259	700
1584 21 rails 3 espaces	36,5	1584	600	556	20,70	13,80	3.044,0	767,0	892,0	674,0	469,0	282,0	1,259	700
1884 25 rails 4 espaces	36,5	1884	450	406	19,40	12,90	2.815,0	710,0	825,0	621,0	430,0	257,0	1,274	700
1884 25 rails 4 espaces	36,5	1884	500	456	21,00	14,00	3.081,0	777,0	903,0	680,0	471,0	281,0	1,273	700
1884 25 rails 4 espaces	36,5	1884	600	556	24,20	16,10	3.610,0	910,0	1.058,0	797,0	553,0	331,0	1,269	1000

05

804 10 rails 1 espace	36,5	804	450	50	8,90	5,90	1.276,0	322,0	374,0	285,0	200,0	122,0	1,224	300
804 10 rails 1 espace	36,5	804	500	50	9,70	6,40	1.396,0	352,0	409,0	311,0	218,0	133,0	1,229	400
804 10 rails 1 espace	36,5	804	600	50	11,20	7,50	1.634,0	412,0	479,0	363,0	254,0	154,0	1,238	400
1224 16 rails 2 espaces	36,5	1224	450	50	13,10	8,70	1.880,0	474,0	551,0	415,0	289,0	173,0	1,265	400
1224 16 rails 2 espaces	36,5	1224	500	50	14,20	9,40	2.061,0	519,0	604,0	455,0	317,0	190,0	1,265	400
1224 16 rails 2 espaces	36,5	1224	600	50	16,40	10,90	2.422,0	611,0	710,0	536,0	372,0	223,0	1,263	700
1584 21 rails 3 espaces	36,5	1584	450	50	16,60	11,00	2.334,0	588,0	684,0	517,0	360,0	216,0	1,258	700
1584 21 rails 3 espaces	36,5	1584	500	50	17,90	11,90	2.569,0	648,0	753,0	569,0	396,0	238,0	1,259	700
1584 21 rails 3 espaces	36,5	1584	600	50	20,70	13,80	3.044,0	767,0	892,0	674,0	469,0	282,0	1,259	700
1884 25 rails 4 espaces	36,5	1884	450	50	19,40	12,90	2.815,0	710,0	825,0	621,0	430,0	257,0	1,274	700
1884 25 rails 4 espaces	36,5	1884	500	50	21,00	14,00	3.081,0	777,0	903,0	680,0	471,0	281,0	1,273	700
1884 25 rails 4 espaces	36,5	1884	600	50	24,20	16,10	3.610,0	910,0	1.058,0	797,0	553,0	331,0	1,269	1000

Thanks to the high performance of Irsap ODDO radiators, the ideal Δt for low temperature projects is Δt at 30°C.


For Δt different from 50°C use the formula: Q=Qn (Δt / 50)n

Standard equipment

- 4 wall fixing in the same color as the radiator
- air vent


Colors and Finishes

STANDARD



Standard White
Cod. 01

CLASSIC




Edelweiss White
Cod. 34



Ivory - RAL 1013
Cod. 02



Beige Cream
Cod. 26



Yellow - RAL 1021
Cod. 04




Melon Yellow - RAL 1028
Cod. E7



Orange - RAL 2004
Cod. 17



Brown Rust - RAL 8004
Cod. E1



Brown - RAL 8017
Cod. 09



Claret - RAL 3003
Cod. 06



Red - RAL 3000
Cod. 05



Strawberry Red - RAL 3018
Cod. Y3



Pink - RAL 3015
Cod. R2



Bluish Lilac - RAL 4005
Cod. R3



Purple Traffic - RAL 4006
Cod. R6




Woodland Green - RAL 6005
Cod. 19



Green Grass - RAL 6018
Cod. N3




Sage Green - RAL 6021
Cod. E6




Pastel Blue - RAL 5024
Cod. G7



Manhattan Grey
Cod. 03




Black - RAL 9005
Cod. 10



Deep Blue
Cod. 2F

SPECIAL



Pearl White
Cod. 16



Quartz 1
Cod. 1C



Sablé
Cod. Y4



Quartz 2
Cod. 2C



Sunstone
Cod. 2D












Tobacco Brown
Cod. 1B



Flame Red
Cod. 7D



Purple Blue
Cod. 1D

							
Azurite 3 Cod. 6C	Medium Grey Cod. 4D	Titanium Grey Metallic - RAL 9023 Cod. L3	Pearl Grey Cod. L6	Graphite Black Cod. 18	Quartz Grey Cod. 31	Satin Black Cod. 30	Matt White Cod. J8
							
Matt Black Cod. K1	Agave Cod. 9N	North Sea Blue Cod. 1P	Ice Cod. 3P	Matt Blue Dove - RAL 5014 Cod. 4P	Matt Light Grey Cod. 8N	Ash Grey - Ral 7021 Cod. G1	Hammered Grey Metallic Cod. 32
							
Hammered Copper Cod. J4							

RAL



Other RAL Colours (following feasibility study)
Cod. ALTRIRAL

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.