

RIGO is a steel radiator with simple lines that avoid cliché. Proportion, elegance, and style all characterize RIGO and make insertion particularly appropriate in the bathroom or kitchen. The dimensions and shapes provide response to extremely precise requirements in terms of space with extra attention dedicated to proportion.



Rigo, Hight 543 mm, Lenght 1520 mm, Ivory - RAL 1013

Construction features

steel towel warmer with 23 mm diameter horizontal round bar heating elements, projection welded on 30 mm manifold threading at the ends of the manifold, first lower pipe, right Gas 1/2"

maximum working pressure 8 bar

maximum working temperature 95°C

Standard equipment

4 wall fixing in the same color as the radiator

1/2" air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C- (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}\text{C}$ (btu/h)	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent	mixed oper. (Watt)
373 9 rails 1 espace	50,0	373	520	470	4,00	2,00	819,0	206,0	240,0	184,0	131,0	81,0	1,184	-
373 9 rails 1 espace	50,0	373	1220	1170	8,30	4,00	1.764,0	445,0	517,0	398,0	283,0	176,0	1,177	-
373 9 rails 1 espace	50,0	373	1520	1470	10,20	4,90	2.208,0	556,0	647,0	499,0	357,0	222,0	1,165	-
543 14 rails 1 espace	50,0	543	520	470	6,00	3,00	1.228,0	310,0	360,0	275,0	195,0	120,0	1,203	-
543 14 rails 1 espace	50,0	543	1220	1170	12,90	6,20	2.648,0	667,0	776,0	595,0	423,0	261,0	1,190	300
543 14 rails 1 espace	50,0	543	1520	1470	15,80	7,60	3.299,0	832,0	967,0	745,0	532,0	331,0	1,169	400
985 25 rails 2 espaces	50,0	985	520	470	10,80	5,40	2.204,0	556,0	646,0	492,0	347,0	212,0	1,216	700
985 25 rails 2 espaces	50,0	985	1220	1170	23,00	11,10	4.719,0	1.189,0	1.383,0	1.058,0	748,0	460,0	1,203	1000
985 25 rails 2 espaces	50,0	985	1520	1470	28,20	13,60	5.855,0	1.476,0	1.716,0	1.318,0	938,0	581,0	1,182	1000

Thanks to the high performance of Irsap RIGO radiators, the ideal Δt for low temperature projects is Δt at 30°C .


For Δt different from 50°C use the formula $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- 4 wall fixing in the same color as the radiator
- 1/2" air vent


Colors and Finishes

STANDARD



Standard White
Cod. 01

CLASSIC




Edelweiss White
Cod. 34



Ivory - RAL 1013
Cod. 02



Beige Cream
Cod. 26



Yellow - RAL 1021
Cod. 04




Melon Yellow - RAL 1028
Cod. E7



Orange - RAL 2004
Cod. 17



Brown Rust - RAL 8004
Cod. E1



Brown - RAL 8017
Cod. 09



Claret - RAL 3003
Cod. 06



Red - RAL 3000
Cod. 05



Strawberry Red - RAL 3018
Cod. Y3



Pink - RAL 3015
Cod. R2



Bluish Lilac - RAL 4005
Cod. R3



Purple Traffic - RAL 4006
Cod. R6




Woodland Green - RAL 6005
Cod. 19



Green Grass - RAL 6018
Cod. N3




Sage Green - RAL 6021
Cod. E6




Pastel Blue - RAL 5024
Cod. G7



Manhattan Grey
Cod. 03




Black - RAL 9005
Cod. 10



Deep Blue
Cod. 2F

SPECIAL



Pearl White
Cod. 16



Quartz 1
Cod. 1C



Sablé
Cod. Y4



Quartz 2
Cod. 2C



Sunstone
Cod. 2D












Tobacco Brown
Cod. 1B



Flame Red
Cod. 7D



Purple Blue
Cod. 1D

							
Azurite 3 Cod. 6C	Medium Grey Cod. 4D	Titanium Grey Metallic - RAL 9023 Cod. L3	Pearl Grey Cod. L6	Graphite Black Cod. 18	Quartz Grey Cod. 31	Satin Black Cod. 30	Matt White Cod. J8
							
Matt Black Cod. K1	Agave Cod. 9N	North Sea Blue Cod. 1P	Ice Cod. 3P	Matt Blue Dove - RAL 5014 Cod. 4P	Matt Light Grey Cod. 8N	Ash Grey - Ral 7021 Cod. G1	Hammered Grey Metallic Cod. 32
							
Hammered Copper Cod. J4							

RAL



Other RAL Colours (following feasibility study)
Cod. ALTRIRAL

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.