

Venus Chrome-plated

IRSAP

The chromed version of VENUS has a strong personality and follows the peculiarities of the modern style. Available in 4 heights and 3 widths, also in the version with 50 mm connections. With the insertion of the electric resistance (optional) it can work even in periods when the system is off.



Venus Cromato, Hight 1720 mm, Lenght 595 mm, Chromium

Construction features

steel towel warmer radiator with horizontal elements featuring
round tubes with a 23 mm diameter
side manifolds with a 40x30 mm semioval section
manifold threading and central connections (50 mm) 1/2" Gas right
maximum working pressure 8 bar
maximum working temperature 95°C

Standard equipment

4 chrome-plated infratube for wall fixing
1/2" chrome-plated air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C- (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}C$ (btu/h)	$\Delta t=50^{\circ}C$ (kcal/h)	$\Delta t=50^{\circ}C$ (Watt)	$\Delta t=40^{\circ}C$ (Watt)	$\Delta t=30^{\circ}C$ (Watt)	$\Delta t=20^{\circ}C$ (Watt)	Exponent	mixed oper. (Watt)
01														
818 15 rails 2 espaces	43,0	818	448	418	4,70	3,50	746,0	188,0	219,0	165,0	114,0	68,0	1,269	-
818 15 rails 2 espaces	48,0	818	497	467	5,00	3,80	815,0	205,0	239,0	180,0	125,0	75,0	1,266	-
818 15 rails 2 espaces	57,0	818	595	565	5,80	4,30	951,0	240,0	279,0	210,0	147,0	88,0	1,258	300
818 15 rails 2 espaces	76,0	818	740	710	8,90	4,80	1.155,0	291,0	338,0	256,0	179,0	108,0	1,247	300
1118 22 rails 2 espaces	43,0	1118	448	418	6,60	5,00	1.077,0	271,0	316,0	238,0	166,0	100,0	1,259	300
1118 22 rails 2 espaces	48,0	1118	497	467	7,20	5,40	1.182,0	298,0	346,0	262,0	182,0	110,0	1,257	400
1118 22 rails 2 espaces	57,0	1118	595	565	8,20	6,10	1.392,0	351,0	408,0	308,0	215,0	129,0	1,253	400
1118 22 rails 2 espaces	76,0	1118	740	710	12,80	6,90	1.706,0	430,0	500,0	379,0	265,0	160,0	1,246	400
1462 28 rails 3 espaces	43,0	1462	448	418	8,50	6,40	1.373,0	346,0	402,0	305,0	213,0	129,0	1,245	400
1462 28 rails 3 espaces	48,0	1462	497	467	9,20	6,90	1.508,0	380,0	442,0	335,0	234,0	141,0	1,247	400
1462 28 rails 3 espaces	57,0	1462	595	565	10,50	7,90	1.780,0	449,0	522,0	395,0	276,0	166,0	1,249	400
1462 28 rails 3 espaces	76,0	1462	740	710	16,30	8,80	2.187,0	551,0	641,0	485,0	338,0	203,0	1,254	700
1720 34 rails 3 espaces	43,0	1720	448	418	10,20	7,70	1.670,0	421,0	489,0	370,0	258,0	156,0	1,251	400

1720 34 rails 3 espaces	48,0	1720	497	467	11,00	8,30	1.837,0	463,0	538,0	407,0	284,0	171,0	1,250	400
1720 34 rails 3 espaces	57,0	1720	595	565	12,60	9,50	2.171,0	547,0	636,0	482,0	336,0	203,0	1,249	700
1720 34 rails 3 espaces	76,0	1720	740	710	19,70	10,60	2.673,0	674,0	783,0	593,0	414,0	250,0	1,246	700
05														
818 15 rails 2 espaces	43,0	818	448	50	4,70	3,50	746,0	188,0	219,0	165,0	114,0	68,0	1,269	-
818 15 rails 2 espaces	48,0	818	497	50	5,00	3,80	815,0	205,0	239,0	180,0	125,0	75,0	1,266	-
818 15 rails 2 espaces	57,0	818	595	50	5,80	4,30	951,0	240,0	279,0	210,0	147,0	88,0	1,258	300
818 15 rails 2 espaces	76,0	818	740	50	8,90	4,80	1.155,0	291,0	338,0	256,0	179,0	108,0	1,247	300
1118 22 rails 2 espaces	43,0	1118	448	50	6,60	5,00	1.077,0	271,0	316,0	238,0	166,0	100,0	1,259	300
1118 22 rails 2 espaces	48,0	1118	497	50	7,20	5,40	1.182,0	298,0	346,0	262,0	182,0	110,0	1,257	400
1118 22 rails 2 espaces	57,0	1118	595	50	8,20	6,10	1.392,0	351,0	408,0	308,0	215,0	129,0	1,253	400
1118 22 rails 2 espaces	76,0	1118	740	50	12,80	6,90	1.706,0	430,0	500,0	379,0	265,0	160,0	1,246	400
1462 28 rails 3 espaces	43,0	1462	448	50	8,50	6,40	1.373,0	346,0	402,0	305,0	213,0	129,0	1,245	400
1462 28 rails 3 espaces	48,0	1462	497	50	9,20	6,90	1.508,0	380,0	442,0	335,0	234,0	141,0	1,247	400
1462 28 rails 3 espaces	57,0	1462	595	50	10,50	7,90	1.780,0	449,0	522,0	395,0	276,0	166,0	1,249	400
1462 28 rails 3 espaces	76,0	1462	740	50	16,30	8,80	2.187,0	551,0	641,0	485,0	338,0	203,0	1,254	700
1720 34 rails 3 espaces	43,0	1720	448	50	10,20	7,70	1.670,0	421,0	489,0	370,0	258,0	156,0	1,251	400
1720 34 rails 3 espaces	48,0	1720	497	50	11,00	8,30	1.837,0	463,0	538,0	407,0	284,0	171,0	1,250	400

1720 34														
rails 3	57,0	1720	595	50	12,60	9,50	2.171,0	547,0	636,0	482,0	336,0	203,0	1,249	700
espaces														
1720 34														
rails 3	76,0	1720	740	50	19,70	10,60	2.673,0	674,0	783,0	593,0	414,0	250,0	1,246	700
espaces														

Thanks to the high performance of Irsap VENUS CHROME-PLATED radiators, the ideal Δt for low temperature projects is Δt at 30°C.

For Δt different from 50°C use the formula: $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- 4 chrome-plated infratube for wall fixing • 1/2" chrome-plated air vent

FINISHES



Chromium
Cod. 50

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.