
XILO 2 is a steel towel radiator with rectangular tubular elements. XILO 2 is available in 4 heights and 5 widths from 456 to 756 mm. With the insertion of the electric resistance (optional) it can work even in periods when the system is off.



Xilo 2, Hight 1744 mm, Lenght 556 mm, Brown Rust - RAL 8004

Construction features

steel towel warmer radiator with horizontal elements featuring
round tubes 18 mm diameter
side manifolds with a 30 mm round section
manifold threading 1/2" Gas right
maximum working pressure 4 bar
maximum working temperature 95°C

Standard equipment

2 pair of CHELA wall brackets
1/2" air vent

Certifications



Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C- (mm)	Weigth (kg)	Capacity (lt)	$\Delta t=50^{\circ}\text{C}$ (btu/h)	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent	mixed oper. (Watt)
792 22 rails 2 espaces	46,0	792	456	406	11,40	4,40	1.819,0	458,0	533,0	409,0	290,0	179,0	1,192	400
792 22 rails 2 espaces	46,0	792	506	456	12,50	4,80	1.986,0	501,0	582,0	446,0	317,0	196,0	1,189	400
792 22 rails 2 espaces	46,0	792	556	506	13,60	5,20	2.153,0	543,0	631,0	484,0	344,0	213,0	1,186	400
792 22 rails 2 espaces	46,0	792	606	556	14,70	5,60	2.320,0	585,0	680,0	522,0	371,0	230,0	1,184	700
792 22 rails 2 espaces	46,0	792	756	706	18,00	6,80	2.821,0	711,0	827,0	636,0	454,0	282,0	1,175	700
1156 32 rails 3 espaces	46,0	1156	456	406	16,60	6,50	2.474,0	624,0	725,0	555,0	393,0	242,0	1,198	700
1156 32 rails 3 espaces	46,0	1156	506	456	18,20	7,00	2.709,0	683,0	794,0	608,0	431,0	266,0	1,195	700
1156 32 rails 3 espaces	46,0	1156	556	506	19,80	7,60	2.944,0	742,0	863,0	661,0	470,0	290,0	1,191	700
1156 32 rails 3 espaces	46,0	1156	606	556	21,40	8,20	3.179,0	801,0	932,0	715,0	508,0	314,0	1,187	1000
1156 32 rails 3 espaces	46,0	1156	756	706	26,20	9,80	3.884,0	979,0	1.138,0	875,0	624,0	387,0	1,177	1000
1520 42 rails 4 espaces	46,0	1520	456	406	21,80	8,50	3.040,0	766,0	891,0	673,0	468,0	281,0	1,259	700
1520 42 rails 4 espaces	46,0	1520	506	456	23,90	9,20	3.329,0	839,0	976,0	739,0	516,0	311,0	1,247	1000
1520 42 rails 4 espaces	46,0	1520	556	506	26,00	10,00	3.619,0	912,0	1.061,0	805,0	565,0	342,0	1,234	1000

1520 42 rails 4 espaces	46,0	1520	606	556	28,10	10,70	3.909,0	985,0	1.146,0	872,0	614,0	374,0	1,222	1000
1520 42 rails 4 espaces	46,0	1520	756	706	34,40	12,90	4.778,0	1.204,0	1.400,0	1.075,0	765,0	473,0	1,184	1000
1744 50 rails 4 espaces	46,0	1744	456	406	25,80	10,00	3.383,0	853,0	992,0	750,0	524,0	315,0	1,250	1000
1744 50 rails 4 espaces	46,0	1744	506	456	28,30	10,90	3.734,0	941,0	1.094,0	830,0	581,0	351,0	1,240	1000
1744 50 rails 4 espaces	46,0	1744	556	506	30,80	11,80	4.085,0	1.030,0	1.197,0	910,0	638,0	388,0	1,231	1000
1744 50 rails 4 espaces	46,0	1744	606	556	33,30	12,70	4.436,0	1.118,0	1.300,0	990,0	697,0	425,0	1,221	1000
1744 50 rails 4 espaces	46,0	1744	756	706	40,80	15,30	5.488,0	1.383,0	1.608,0	1.233,0	875,0	539,0	1,193	1000

Thanks to the high performance of Irsap XILO 2 radiators, the ideal Δt for low temperature projects is Δt at 30°C.


For Δt different from 50°C use the formula: Q=Qn (Δt / 50)n

Standard equipment

- 2 pair of CHELA wall brackets
- 1/2" air vent


Colors and Finishes

STANDARD



Standard White
Cod. 01

CLASSIC




Edelweiss White
Cod. 34



Ivory - RAL 1013
Cod. 02



Beige Cream
Cod. 26



Yellow - RAL 1021
Cod. 04




Melon Yellow - RAL 1028
Cod. E7



Orange - RAL 2004
Cod. 17



Brown Rust - RAL 8004
Cod. E1



Brown - RAL 8017
Cod. 09



Claret - RAL 3003
Cod. 06



Red - RAL 3000
Cod. 05



Strawberry Red - RAL 3018
Cod. Y3



Pink - RAL 3015
Cod. R2



Bluish Lilac - RAL 4005
Cod. R3



Purple Traffic - RAL 4006
Cod. R6




Woodland Green - RAL 6005
Cod. 19



Green Grass - RAL 6018
Cod. N3




Sage Green - RAL 6021
Cod. E6




Pastel Blue - RAL 5024
Cod. G7



Manhattan Grey
Cod. 03




Black - RAL 9005
Cod. 10



Deep Blue
Cod. 2F

SPECIAL



Pearl White
Cod. 16



Quartz 1
Cod. 1C



Sablé
Cod. Y4



Quartz 2
Cod. 2C



Sunstone
Cod. 2D












Tobacco Brown
Cod. 1B



Flame Red
Cod. 7D



Purple Blue
Cod. 1D

							
Azurite 3 Cod. 6C	Medium Grey Cod. 4D	Titanium Grey Metallic - RAL 9023 Cod. L3	Pearl Grey Cod. L6	Graphite Black Cod. 18	Quartz Grey Cod. 31	Satin Black Cod. 30	Matt White Cod. J8
							
Matt Black Cod. K1	Agave Cod. 9N	North Sea Blue Cod. 1P	Ice Cod. 3P	Matt Blue Dove - RAL 5014 Cod. 4P	Matt Light Grey Cod. 8N	Ash Grey - Ral 7021 Cod. G1	Hammered Grey Metallic Cod. 32
							
Hammered Copper Cod. J4							

RAL



Other RAL Colours (following feasibility study)
Cod. ALTRIRAL

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.