



technical data

fly


Ref.	A	B	C	White & Colors		Weight	Cap.	Recommended Resistances			
				$\Delta t=50^{\circ}\text{C}$	$\Delta t=30^{\circ}\text{C}$			Erforderliche Widerstände			
				W	W			Résistances Conseillés			
	mm	mm	mm			kg	Lt	Resistencias Recomendadas			
								300W	500W	750W	1000W
820 9 elements éléments elementos	FY082045	838	450	400	378	206	7,1	3,3	●		
	FY082050	838	500	450	411	224	7,7	3,5	●		
	FY082060	838	600	550	476	260	9,0	4,0		●	
	FY082075	838	750	700	575	313	10,9	4,8		●	
1200 13 elements éléments elementos	FY120045	1218	450	400	506	276	10,2	4,7		●	
	FY120050	1218	500	450	559	305	11,2	5,1		●	
	FY120060	1218	600	550	665	362	13,0	5,9		●	
	FY120075	1218	750	700	824	448	15,7	7,0			●
1500 16 elements éléments elementos	FY150045	1522	450	400	619	337	12,7	5,9		●	
	FY150050	1522	500	450	685	373	13,8	6,3			●
	FY150060	1522	600	550	816	443	16,0	7,2			●
	FY150075	1522	750	700	1013	549	19,4	8,6			●
1800 20 elements éléments elementos	FY180045	1826	450	400	744	405	15,7	7,3			●
	FY180050	1826	500	450	819	445	17,1	7,8			●
	FY180060	1826	600	550	968	525	19,9	8,9			●
	FY180075	1826	750	700	1193	645	24,1	10,6			●

kcal/h = 0,86 x Watt

● White & Color


Wall fastening systems

Befestigungssysteme an der Wand
Systèmes d'installation murale
Sistemas de fijación a la pared




Radiator body dimensions

Größe des Heizkörpers
Dimensions du corps chauffant
Dimensiones del cuerpo calefactor



Installation with heating element and "T"

Installation gemischter Ausführung mit "T"
Installation avec résistance électrique et "T"
Instalación con resistencia eléctrica y "T"




"T" fitting
T-Stück
Raccord en "T"
Conexión en "T"

Resistance with thermostat
Widerstand mit Thermostat
Résistance avec thermostat
Resistencia con termostato

Modification of interaxis with "T" fitting
Achsabstandänderung durch T-Stück
Variation interaxe avec raccord "T"
Variación entreje con rācor en "T"

Measures in mm: A=height B=width C=interaxis
Abmessungen in mm: A=Höhe B=Breite C=Achsabstand
Mesures en mm: A=hauteur B=largeur C=entraxe
Medidas en mm: A=altura B=ancho C=entre eje



technical notes

Maximum operating temperature: 90 °C
Max. Betriebstemperatur: 90° C
Température maximum de fonctionnement: 90 °C
Temperatura máx de funcionamiento: 90 °C

Maximum operating pressure: 400 kPa
Max. Betriebsdruck: 400 kPa
Pression maximum de fonctionnement: 400 kPa
Presión máx de funcionamiento: 400 kPa



Wall fastening systems are white for "9010" version, chromed for "colors" versions
Die Befestigungselemente sind für die Ausführung "9010" weiß und für Ausführungen "colours" verchromt
Les systèmes d'installation sont blanc pour la version "9010", chromés pour les versions "colors"
Los sistemas de fijación son blancos para la versión "9010", cromados para las versiones "colors"

For single pipe installation, please consult technical notes Pag. 163
Bei dem Einrohrsystem lesen Sie die technischen Daten auf Seite 165
Pour installation monotube consulter les renseignements techniques détaillés Pag. 167
Para instalaciones monotubo consulte las informaciones técnicas detalladas Pag. 169